

Sistema dinámico de fijación para uniones empernadas						
tabla de dimensiones de arandelas estandar de acero con protección MAGNI 515						
código	diam. Int.	toler.	diam. Ext.	toler.	espesor	toler.
CMC 3	3,4	±0.1mm	7,0	±0.2mm	1,8	±0.25mm
CMC 3.5	3,9	±0.1mm	7,6	±0.2mm	1,8	±0.25mm
CMC 4	4,4	±0.1mm	7,6	±0.2mm	1,8	±0.25mm
CMC 5	5,4	±0.1mm	9,0	±0.2mm	1,8	±0.25mm
CMC 6	6,5	±0.1mm	10,8	±0.2mm	1,8	±0.25mm
CMC 1/4"	7,2	±0.1mm	11,5	±0.2mm	1,8	±0.25mm
CMC 8	8,7	±0.1mm	13,5	±0.2mm	2,5	±0.25mm
CMC 3/8"	10,3	±0.1mm	16,6	±0.2mm	2,5	±0.25mm
CMC 10	10,7	±0.2mm	16,6	±0.2mm	2,5	±0.25mm
CMC 11	11,4	±0.2mm	18,5	±0.2mm	2,5	±0.25mm
CMC 12	13,0	±0.2mm	19,5	±0.2mm	2,5	±0.25mm
CMC 1/2"	13,5	±0.2mm	19,5	±0.2mm	2,5	±0.25mm
CMC 14	15,2	±0.2mm	23,0	±0.2mm	3,4	±0.25mm
CMC 16	17,0	±0.2mm	25,4	±0.2mm	3,4	±0.25mm
CMC 18	19,5	±0.2mm	29,0	±0.2mm	3,4	±0.25mm
CMC 3/4"	20,0	±0.2mm	30,7	±0.2mm	3,4	±0.25mm
CMC 20	21,4	±0.2mm	30,7	±0.2mm	3,4	±0.25mm
CMC 22	23,4	±0.2mm	34,5	±0.2mm	3,4	±0.25mm
CMC 24	25,3	±0.2mm	39,0	±0.2mm	3,4	±0.25mm
CMC 1"	27,9	±0.2mm	39,0	±0.2mm	3,4	±0.25mm
CMC 27	28,4	±0.2mm	42,0	±0.3mm	6,6	+0/-0.5mm
CMC 30	31,4	±0.2mm	47,0	±0.3mm	6,6	+0/-0.5mm
CMC 33	34,4	±0.2mm	48,5	±0.3mm	6,6	+0/-0.5mm
CMC 36	37,4	±0.2mm	55,0	±0.3mm	6,6	+0/-0.5mm
CMC 39	40,4	±0.2mm	58,5	±0.3mm	6,6	+0/-0.5mm
CMC 42	43,2	±0.2mm	63,0	±0.3mm	6,6	+0/-0.5mm
CMC 45	46,2	+0.5/-0mm	70,0	+0/-2.0mm	7,0	±0.75mm