

<b>Sistema dinámico de fijación para uniones empernadas</b>						
<b>tabla de dimensiones de arandelas estandar de acero inoxidable</b>						
<b>código</b>	<b>diam. Int.</b>	<b>toler.</b>	<b>diam. Ext.</b>	<b>toler.</b>	<b>espesor</b>	<b>toler.</b>
CMC 3 SS	3,4	±0.1mm	7,0	±0.2mm	1,8	±0.25mm
CMC 3.5 SS	3,9	±0.1mm	7,6	±0.2mm	1,8	±0.25mm
CMC 4 SS	4,4	±0.1mm	7,6	±0.2mm	1,8	±0.25mm
CMC 5 SS	5,4	±0.1mm	9,0	±0.2mm	1,8	±0.25mm
CMC 6 SS	6,5	±0.1mm	10,8	±0.2mm	1,8	±0.25mm
CMC 1/4" SS	7,2	±0.1mm	11,5	±0.2mm	1,8	±0.25mm
CMC 8 SS	8,7	±0.1mm	13,5	±0.2mm	2,5	±0.25mm
CMC 3/8" SS	10,3	±0.1mm	16,6	±0.2mm	2,5	±0.25mm
CMC 10 SS	10,7	±0.2mm	16,6	±0.2mm	2,5	±0.25mm
CMC 11 SS	11,4	±0.2mm	18,5	±0.2mm	2,5	±0.25mm
CMC 12 SS	13,0	±0.2mm	19,5	±0.2mm	2,5	±0.25mm
CMC 1/2" SS	13,5	±0.2mm	19,5	±0.2mm	2,5	±0.25mm
CMC 14 SS	15,2	±0.2mm	23,0	±0.2mm	3,4	±0.25mm
CMC 16 SS	17,0	±0.2mm	25,4	±0.2mm	3,4	±0.25mm
CMC 18 SS	19,5	±0.2mm	29,0	±0.2mm	3,4	±0.25mm
CMC 3/4" SS	20,0	±0.2mm	30,7	±0.2mm	3,4	±0.25mm
CMC 20 SS	21,4	±0.2mm	30,7	±0.2mm	3,4	±0.25mm
CMC 22 SS	23,4	±0.2mm	34,5	±0.2mm	3,4	±0.25mm
CMC 24 SS	25,3	±0.2mm	39,0	±0.2mm	3,4	±0.25mm
CMC 1" SS	27,9	±0.2mm	39,0	±0.2mm	3,4	±0.25mm
CMC 27 SS	28,4	±0.2mm	42,0	±0.3mm	6,6	+0/-0.5mm
CMC 30 SS	31,4	±0.2mm	47,0	±0.3mm	6,6	+0/-0.5mm
CMC 33 SS	34,4	±0.2mm	48,5	±0.3mm	6,6	+0/-0.5mm
CMC 36 SS	37,4	±0.2mm	55,0	±0.3mm	6,6	+0/-0.5mm
CMC 39 SS	40,4	±0.2mm	58,5	±0.3mm	6,6	+0/-0.5mm
CMC 42 SS	43,2	±0.2mm	63,0	±0.3mm	6,6	+0/-0.5mm
CMC 45 SS	46,2	+0.5/-0mm	70,0	+0/-2.0mm	7,0	±0.75mm